

AT-D13R3



Main Features

- ⇒ 1/3" 1.3MP PS CMOS Image Sensor
- ⇒ Max 25fps@1.3MP
- ⇒ H.264 and MJPEG Triple-stream encoding
- ⇒ DWDR, Day/Night(ICR), 2D/3D-DNR, AWB, AGC, BLC
- ⇒ 2.8mm fixed lens
- ⇒ IR Range of 30 Mtrs, IP66, PoE
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



SPECIFICATION - AT-D13R3

MODEL	AT-D13R3
Image Sensor	1/3" 1.3MP PS CMOS Image Sensor
Minimum Illumination	Colour: 0.02 Lux (F1.8, AGC ON), 0 Lux with IR
Shutter Speed	Auto/Manual, 1/6s~1/8000s
White Balance	Auto/Manual
Lens	2.8mm
Agc	Auto/Manual
Video Compression	H.264/MJPEG
BLC	BLC/HLC/WDR(120db)
S/N Ratio	>50dB
Video Streaming	Tripple
Frame Rate	1.3MP(1280x960)/720P(1280x720)/D1720x576) @ 25 fps
Motion Detection	Up to 2 areas
Privacy Mask	Up to 4 areas
ICR	IR-cut filter with auto switch (ICR)
Protocol	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,Qos,DNS,DDNS,NT P,FTP,UPnP,HTTP, Onvif
Resolution	2MP @ 25fps
Ethernet	1 RJ45 10M/100M Base-TX Ethernet
OSD	UP TO 8 OSDS
IR	IR range of 30 Mtr
Operating Temperature	-35°C ~ +60°C (-31°F ~ 140°F)
Humidity	≤ 90% RH(non-condensing)
Power Source	12 V DC or PoE (IEEE802.3 af)
Power Consumption	3.5 W (5.5W with IR on)
Weatherproof Standard	IP66
Dimension	Φ126 x 94 mm (Ø5.0" x 3.7")
Weight	0.33kg