



AT-2020L10-M



Main Features

- ⇒ 1/2.8" 2 MP PS Image Sensor
- ⇒ Powerful 20x Optical Zoom
- ⇒ Third Generation Infrared Technology
- ⇒ Up to 255 Presets, 16 patrol, 16 Pattern
- ⇒ Max 240°/s pan speed, 360° endless pan rotation
- ⇒ IR Range of 100 Mtr., Micro SD
- ⇒ Built-in 1/1 alarm in/out, IP66
- ⇒ Mobile Software for Android, iOS
- ⇒ CMS Software: IVMS



SPECIFICATION - AT-2020L10-M

MODEL	AT-2020L10-M
Image Sensor	1/2.8" 2MP CMOS
Effective Pixel	1920(H) x 1080(V)
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
White Balance	Auto/Manual
S/N Ratio	more than 52dB
Minimum Illumination	Color: 0.03 lux (F1.6, 50IRE), B/W: 0.01 lux (F1.6, 50IRE)
Focal Length	4.7mm~94mm
Focus Control	Auto / Manual
Angle of View	61.9° (wide) ~ 3.5° (tele)
Iris Control	Auto/Manual; F1.6 ~ F3.3
Electronic Shutter	Auto/Manual; shutter time: 1/16 s ~ 1/8000 s
Agc	Auto/Manual
Optical Zoom	20x
Digital Zoom	Supports
Pan Travel	360° endless, Pan Speed: 0.1°/s ~ 240°/s
Tilt Travel	-15° ~ 90°, Tilt Speed: 0.1° ~160°/sec
Preset	255
Preset speed	Pan: 300° /s; Tilt: 240° /s
Special Features	IR Range upto 100m, Up to 256 Presets, 16 Patrol, 16 Pattern
privacy masking	up to 8 areas
Day/Night:IR Cut Filter	IR-cut filter with auto switch (ICR)
Video Compression	H.264 / MJPEG
Video Streaming	1080P(1 ~ 25/30fps) Triple Stream
Audio Comprerssion	G.711a
Audio Streaming	Two way Talk Supported
Protocol	L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP, NTP,FTP,HTTP,SNMP,SIP
Operating Temperature	-40°C ~ +65°C (-40°F ~ 149°F), Humidity ≤ 90% RH(non-condensing)
Weatherproof Standard	IP66
Dimension	Ø227 x 359.4 mm (Ø8.9" x 14.2")
Weight	5.28kg